



SK 11 RIG INFORMATION

Entrepose Drilling SK 11 is highly mobile, trailer mounted workover rig. In addition to being manufactured under full API and EC regulations, the rigs have been designed to reduce environmental impact. The rig offer a reduced footprint and is easy to mobilize. The SK11 has a long track record in workovers on geothermal and oil & gas wells.



SK11 RIG INFORMATION

MAST

Type	Skytop 56 – 120 XF
Height	17,10 m
Max. Hook Load	45 metric tonnes
Max. Dyn. Load	33 metric tonnes

DRAWWORKS

Type	Skytop H1 32-32
Capacity	228 HP
Max rpm	211 rpm
Breaking load	41,1 Kgf

TRAVELLING BLOCK

Type	Mac Kissick
Model	82 A
Capacity	50 T

BLOW OUT PREVENTION EQUIPMENT

Type	Hydril
Diameter	4 1/16 to 13 3/8"

MUD SYSTEM

Active tank	2 x 25 m3 with hooper
Mixing tank	4 m3
Mud pump	1 x Gardner Denver 800 l/min 1000 PSI 400 l/min 2750 PSI

TRAILER

Type	Unic 2764
PTC	26 T
Rear axle	2

ADDITIONAL EQUIPMENT

Power Swivel	Bowen 1.5
Generator	65 Kva - soundproof
2600 m tubings 2 7/8"	
Diesel fuel tank, compressor unit	
Offices, crew cabins, workshops etc.	
Surface eqpt (HP cleaning, etc.)	